

WALNUT CANYON™

GLAZED PORCELAIN

REVEAL IMAGING®

MARAZZI
DARE TO BE BOLD™

FLOOR TILE



Cream



Golden



Multi




Umber

2 x 2 SQUARE MOSAIC - 13 x 13 SHEET



Cream



Golden



Multi



Umber

2 x 4 BRICK JOINT MOSAIC - 13 x 13 SHEET



Cream



Golden



Multi








Umber

USAGE

Floors	Walls	Countertops
F	W	C

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	20 x 20 Floor Tile	(19-11/16" x 19-11/16") (50.00 cm x 50.00 cm)	3/8"	18.83	7
	13 x 13 Floor Tile	(13-1/8" x 13-1/8") (33.30 cm x 33.30 cm)	5/16"	17.90	15
	6-1/2 x 6-1/2 Floor Tile	(6-1/2" x 6-1/2") (16.50 cm x 16.50 cm)	5/16"	10.55	36
	2 x 4 Brick Mosaic (Mesh-mounted)	(13" x 13" Sheet) (33.30 cm x 33.30 cm)	3/8"	10.00	10
	2 x 2 Square Mosaic (Mesh-mounted)	(13" x 13" Sheet) (33.30 cm x 33.30 cm)	3/8"	10.00	10

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■
Wet & Level – Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	■*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazzitile.com/DCOF.

APPLICATION NOTES:


Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed

*Mosaic tile only.

TRIM

Description	Size	Shape
Floor Bullnose	3 x 13	

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) Mosaic: 1/8"	 Random Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor/Mosaic Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	7.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	IV

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit marazzitile.com.

	Floor Tile			Deco		Trim
	20 x 20	13 x 13	6-1/2 x 6-1/2	2 x 4 Brick-Joint Mosaic 13 x 13 Sheet	2 x 2 Square Mosaic 13 x 13 Sheet	3 x 13 Floor Bullnose
Cream	UJ3V	UJ3U	UJ3W	UJ35	UJ34	UJ3Y
Golden	UHC6	UHC3	UHDQ	UHD7	UHD4	UHDW
Multi	UHC7	UHC4	UHDR	UHD8	UHD5	UHDX
Umber	UHC5	UHC2	UHDP	UHD6	UHD3	UHDV



Floor Tile



Wall Tile



Reveal Imaging®



Pre-Consumer
Recycled Content

